HDMI® AUDIO DE-EMBEDDER WITH





CS-HDMABOD HDMI[®] AUDIO DE-EMBEDDER WITH DOWN MIXING

SALES 386-255-0234

PRODUCT OVERVIEW

The CS-HDMABOD allows you to take an HDMI® source and de-embed the audio for use on either an optical audio connection or stereo RCA analog connection, all while still passing audio through on the HDMI® output, preserving the quality of sound. This de-embedder can also down mix multi-channel bitstream audio to stereo output to allow you to maintain 5.1 surround audio on the HDMI output. This next-generation product has been engineered with updated functionality to support HDMI® 2.0, HDCP 2 .2 (and earlier versions), and support 1080p, 3D, and 4K/60Hz 4:4:4 up to 18Gbps.

- Easily obtain an analog or digital audio output connection from an existing HDMI® source
- Selectable HDMI® audio on HDMI® output for native pass-through, 5.1 CH or 2 CH
- Audio outputs: optical audio and stereo RCA analog
- Optical digital audio supports LPCM 2CH, Dolby Digital 2/5.1CH, DTS 2/5.1CH
- CEC pass through
- Supports HDMI® 2.0 and HDCP 2.2 (and earlier versions)
- Supports 1080p, 3D, 4K/60Hz 4:4:4 up to 18Gbps

